


# Product data sheet

M10 - RECESSED - UGR<LT/>16 3000K CRI 90 24W CLD WHITE  
22190110-39  
DISANO



Housing: in steel plate. Optics: anti-glare for improved visual comfort. : UGR<lt/>19, according to standard EN 12464. Coating: epoxy polyester powder coating resistant to UV rays. Heat Sink: built-in. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: galvanised steel wire springs for false ceiling mounting. On request: version with 15° or 30° beams. Available with different aesthetic finishes to create surprising lighting effects.

## Light output 1



1 x LED

Nominal lamp power	24 W	LOR	100%
Lamp flux	1895 lm	Total flux	1895 lm
Luminous efficacy	79 lm/W	Total power	24 W
CCT	3000 K		
CRI	90		

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 11.02 in

Width: 1.97 in

Height: 2.56 in

## Adjustability

Fixed

## Design

Material impression: Aluminum

Color of housing: White

## Electric

System power: 24 W

Appliance Class: II

## Protection

IP: 40

IK: 07

Designation labels: CE