


Product data sheet

BASIC MAX SURFACE - Y1
BY10SE-830E-D900
LIGHTNET



LED surface-mounted luminaire for walls or ceilings. Direct light distribution and indirect lighting corona or direct only light distribution. 6 different diameters from 300mm to 1200mm. Surface white, silver, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting with maximum transmittance and homogeneous lighting. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial $\leq$ MacAdam 3. Colour rendering CRI>80 or CRI>90. On request: Integration of emergency lighting components, sensor technology.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	59 W	CRI	82
Total flux	6545 lm	LOR	100%
Luminous efficacy	111 lm/W	Total power	59 W

Mounting mode

Ceiling mounted

Electric

System power: 59 W

Shape and measurements

Height: 35.43 in

Diameter: 35.43 in

Protection

Adjustability

Fixed