Product data sheet

ROTAO60 227-2D0I-10GEE/840, S
227-2D0I-10GEE/840
HALLA



IP 20

227-2D0I-10GEE/840, S Luminaire surface Material of luminaire: Colour of luminaire: Shape of luminaire: Circular Size: 2050 x 2050 x 65 mm Type of installation: Surface Distribution: Direct Optics type: Microprisma Protection class: I Voltage: 220-240V

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	8.4 W	CRI	80
Total flux	720 lm	LOR	100%
Luminous efficacy	86 lm/W	Total power	8.4 W

Light outputs 2..5 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	8.4 W	CRI	80
Total flux	720 lm	LOR	100%
Luminous efficacy	86 lm/W	Total power	8.4 W

Light output 6 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	8.4 W	CRI	80
Total flux	720 lm	LOR	100%
Luminous efficacy	86 lm/W	Total power	8.4 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	8.4 W	CRI	80
Total flux	720 lm	LOR	100%
Luminous efficacy	86 lm/W	Total power	8.4 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	8.4 W	CRI	80
Total flux	720 lm	LOR	100%
Luminous efficacy	86 lm/W	Total power	8.4 W

Light output 9 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	8.4 W	CRI	80
Total flux	720 lm	LOR	100%
Luminous efficacy	86 lm/W	Total power	8.4 W

Light output 10 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	8.4 W	CRI	80
Total flux	720 lm	LOR	100%
Luminous efficacy	86 lm/W	Total power	8.4 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Height: 2.56 in

Diameter: 80.71 in

Adjustability

Fixed

Electric

System power: 84 W

Appliance Class: I

Protection

IP: 20