Product data sheet

FLUMO60-S 228S-260I-120GE/840, B
228S-260I-120GE/840
HALLA



IP 20 IK 01

228S-260I-120GE/840, B Luminaire surface/suspended Material of luminaire: Colour of luminaire: Shape of luminaire: Rounded Size: 632 x 60 x 65 mm Type of installation: Surface, Suspended Distribution: Direct Optics type: Microprisma Protection class: I Voltage: 220-240V

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.75 W	CRI	80
Total flux	198 lm	LOR	100%
Luminous efficacy	72 lm/W	ULOR	2%
		Total power	2.75 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.75 W	CRI	80
Total flux	198 lm	LOR	100%
Luminous efficacy	72 lm/W	ULOR	2%
		Total power	2.75 W

Light output 3 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.75 W	CRI	80
Total flux	198 lm	LOR	100%
Luminous efficacy	72 lm/W	ULOR	2%
		Total power	2.75 W

Light output 4 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.75 W	CRI	80
Total flux	198 lm	LOR	100%
Luminous efficacy	72 lm/W	ULOR	2%
		Total power	2.75 W

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 5.91 in
Width: 2.36 in
Height: 2.56 in

Adjustability

Fixed

Electric

System power: 11 W
Appliance Class: I

Protection

IP: 20
IK: 01