Product data sheet


CIRCULAR OUTWARD 3 RINGS (Ø900 Ø2000 Ø900)
CF4O-00W9AZRU14
LEDSC4



IP 20

LedsC4 Circular Outward 3 Rings (ø900 ø2000 ø900) CF4O-00W9AZRU14V1 Pendant for indoor use. For sideways lighting. Structure finish: White. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 0 Product width or diameter (mm): 2042 Product height (mm): 6500 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEANWELL. Maximum power of light source: 209.2W. Colour temperature: 3000K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. Photobiological risk: RG1. Real flux (lm): 15283. Real lm/W: 71. Voltage / frequency range: 90-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 216. Power factor: 0.90. Dimmable equipment included: 0-10V.


Light output 1



1 x LED

Nominal lamp power	44.4 W	LOR	100%
Lamp flux	2770 lm	ULOR	49%
Luminous efficacy	62 lm/W	Total flux	2770 lm
CCT	3000 K	Total power	44.4 W
CRI	90		


Light output 2



1 x LED

Nominal lamp power	44.4 W	LOR	100%
Lamp flux	2770 lm	ULOR	49%
Luminous efficacy	62 lm/W	Total flux	2770 lm
CCT	3000 K	Total power	44.4 W
CRI	90		

Light output 3



1 x LED

Nominal lamp power	127.2 W	LOR	100%
Lamp flux	9743 lm	ULOR	49%
Luminous efficacy	77 lm/W	Total flux	9745 lm
CCT	3000 K	Total power	127.2 W
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 35.43 in
Width: 35.43 in
Height: 1.18 in

Adjustability

Fixed

Electric

System power: 216 W
Appliance Class: I

Protection

IP: 20