


Product data sheet

CIRCULAR OUTWARD Ø3000 SURFACE
CF4D-00A9AZDU05
LEDSC4



LedsC4 Circular Outward ø3000 Surface CF4D-00A9AZDU05V1 Pendant for indoor use. For sideways lighting. Structure finish: Black. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 18 Product width or diameter (mm): 2998 Product height (mm): 5000 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEAN WELL. Maximum power of light source: 180.8W. Colour temperature: 2400K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 4.8. Photobiological risk: RG0. Real flux (lm): 12111. Real lm/W: 64. Voltage / frequency range: 90-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 190. Power factor: 0.90. Dimmable equipment included: DALI-2/PUSH.

Light output 1



1 x LED			
Nominal lamp power	190 W	LOR	100%
Lamp flux	12111 lm	ULOR	49%
Luminous efficacy	64 lm/W	Total flux	12113 lm
CCT	2400 K	Total power	190 W
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 118.11 in

Width: 118.11 in

Height: 1.18 in

Adjustability

Fixed

Electric

System power: 190 W

Appliance Class: I

Protection

IP: 20