



Product data sheet

CEILING AND WALL MOUNTED LUMINAIRE SLASH 2 HPE (HIGH PERFOR
2006.3905 - SLASH2 CW602 LED980-840 DIR ELOX ONF
REGENT



Ceiling and wall mounted luminaire Slash 2 HPE (High Performance Efficiency), with LED, system power: 11 W, luminous flux of luminaire 980 lm, colour rendering index CRI > 80, colour temperature 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L80 75'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct light emission, luminaire profile in aluminium natural-colour anodised diffuser in polycarbonate (PC), APD (Added Performance Diffuser), OpalLed, 1 integral control gear, ON/OFF, Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0281), luminaire complies with the strict requirements for Minergie-certified luminaires protection class I, ingress protection IP20, glow wire test 850 °C, impact strength: IK 08 this product contains a light source of energy efficiency class B and EPREL registration number: 1249140 L = 602 mm, B = 48 mm,

Light output 1



1 x LED			
Nominal lamp power	20 W	LOR	100%
Lamp flux	980 lm	Total flux	980 lm
Luminous efficacy	49 lm/W	Total power	11 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 23.70 in

Width: 1.89 in

Height: 2.76 in

Weight: 2.865 kg

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 11 W

Appliance Class: I

Protection

IP: 20

IK: 08