Product data sheet

SRT-SYSTEM IP64-SRGSVCTB PP/1500 LED - GERÄTETRÄGER VARIABEL CENTRAL.LINE.OPTIC | DEVICE MOUNT VARIAB.. 14000-9000 840 14382LM IP64 ETM SW RAL 9005 (SRT+19537004914)


REGIOLUX



IP 64 IK 03 CE

SRT-Quick-fit mounting system, IP 64 variable device mount, Modullänge/1500. Device mounts made of galvanised, profiled sheet steel with zinc coating combined with polyester resin paint guarantees good corrosion protection; tool-free attachment with design-integrated push locks ensure protection against theft and disassembly. Integrated end faces made of plastic with sealing lips and an all-round closed seal to the support rail for a protection type up to IP64. Variable position on the support rail. Housing colour black RAL 9005. Performance level: Powerful Performance (PP) - Powerful, universal all-rounder, sets very high standards for efficiency, service life and warranty period, Light distribution direct narrow/wide distribution by means of Central.Line.Optic of PMMA plastic, The lens optics ensure ease of installation and are easy to maintain thanks to the easy-to-clean surface. The density of the single-row lens arrangement ensures that the points merge into a line with a homogeneous appearance in the object. The light source and driver are removable in accordance with the EU 2019/2020 ecodesign requirements and can be replaced in the factory. Electrical connection by means of a 1m connection cable for variable device mount positioning with a 3-pin, quick-fit plug connector in the light run with free phase pre-selection. The device mount can be adjusted variably in steps with a multi-lumen driver. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system. Additional information on the driver switching stages is available on the Internet on the product details page or in the product data sheet under the heading Operating Data. Dimensions (LxWxH): 1535mm x 55mm x 37mm Beam angle: 80°(C0)/80° (C90) Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 4000K Colour tolerance: 3SDCM Photobiological safety (Luminaire): RG1 Nominal luminous flux/switching steps (rounded): 8700lm/49W, 11000lm/64W, 12700lm/76W, 14400lm/88W (Standard setting 14382lm) Luminaire luminous efficiency: 177lm/W-164lm/W Control gear: Electronic multi-lumen driver, 4-steps (1 pcs.) System output: 88W-49W Energy efficiency class/light source: B Mains voltage: 230V Mains frequency: 50Hz Impact resistance (IK rating): IK03 (-20°C bis 40°C) Ambient temperatur: ta -20°C to 40°C UGR lat./long.: 22.3 / 21.4 (88W) Certification mark: IP64, Protection class I, ENEC10 VDE, F, D, HACCP DIN10500/Food/IFS-application-related suitability (see certificate)/BRC, Indoor, CE Warranty period: 7 years Regiolux GmbH Type: SRGSVCTB PP /1500 LED 14000-9000 840 ETM sw RAL 9005 Article number: 19537004914 Product deep link: https://www.regiolux.de/en/article/19537004914 General warranty conditions: www.regiolux.de/en/Service/Warranty

Light output 1 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	87.8 W	CRI	80
Total flux	14382 lm	LOR	100%
Luminous efficacy	164 lm/W	Total power	87.8 W

Mounting mode

Ceiling mounted, Contact rail

Electric

System power: 87.8 W

Appliance Class: 0

Shape and measurements

Length: 60.43 in

Width: 2.48 in

Height: 2.64 in

Design

Color of housing: Black

Protection

IP: 64

IK: 03

Designation labels: CE, ENEC