


# Product data sheet

3F HD50DI BK 16+26/840 DALI 5P FD L1468 + FDO


6577+A01542

3F FILIPPI



ILLUMINOTECHNICAL Luminous efficiency 100% (DLOR 32%, ULOR 68%). Initial luminous flux of the luminaire 5009 lm. Direct-indirect distribution. Installation Interdistance Transv.D = 1.40 x hu - Long.D = 1.20 x hu. Tabular UGR (CIE 117 - 4H-8H; S=0.25H; 70/50/20): RUG 19.8 - 17.3. Beam angle: 112° - 114°. Luminous efficacy 109 lm/W. Lifetime (L93/B10): 30000 h. (tq+25°C) Lifetime (L90/B10): 50000 h. (tq+25°C) Lifetime (L85/B10): 80000 h. (tq+25°C) Lifetime (L80/B10): 100000 h. (tq+25°C) Sudden decreased luminous flux after 50000 hours: 0% (C0). Photobiological safety in compliance with IEC/TR 62778: RG0 risk exempt, (IEC 62471). In compliance with IEC/EN 62722-2-1 - IEC/EN 62717 standards. SOURCE 2 linear LED modules 16+26W/840. Energy efficiency class (UE 2019/2020 - UE 2019/2015): D. CIE 13.3 Colour rendering index: CRI >80 (R9 <50%). IES TM-30 Fidelity Index: Rf = 84 Rg = 95. CCT nominal colour temperature 4000 K. Colour initial tolerance (MacAdam): SDCM 3. MECHANICAL Extruded aluminium housing. Black colour body RAL 9011 matt. Removable gear-tray. Hot-dip galvanised steel linear connecting element installed on the body for rapid mechanical connection. Non-iridescent high efficiency specular aluminium with a titanium and magnesium surface treatment flow recuperator. Translucent polycarbonate upper diffuser. Luminaire with limited surface temperature. - D - (EN 60598-2-24) Dimensions: 1468x57 mm, height 80 mm. Weight 4.127 kg. IP40 protection degree. Mechanical strength to impacts IK02 (0.2 joule). Glow-wire test resistance 650°C. ELECTRICAL Halogen Free DALI, PUSH-DIM, electronic wiring 230V-50/60Hz, power factor 0.90 at full load, THD <25%, constant output current, SELV, class I, 2 driver, 2 DALI addresses. Power of the luminaire 46 W. CE - IEC 60598-1 - EN 60598-1. SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC. Ambient temperature from 0°C to +25°C. Temperature class T6 max 85°C. Entrance to the upper power supply in proximity to a power head. 5-pole terminal block, single 230V circuit. 5 mm² section 2.5 pin through line with an irreversible quick coupling plug plug/socket fixed on the body for rapid electrical connection. Branching via an irreversible quick coupling plug to connect the cable housing element to the socket. Relative humidity UR: <85%. INSTALLATION Suspended. In the channel versions, the FastWiring system drastically reduces the installation time. All accessories dedicated to this product are available on the Catalog and on our website [www.3F-Filippi.com](http://www.3F-Filippi.com). ACCESSORIES FDO - Flat diffuser, smooth outside and made of opal polycarbonate. Supplied in roll. APPLICATIONS Environments: architectural, commercial, staterooms, banks. Environments where soft diffuse light is required for optimal visual comfort and total shielding of the source. LIGHT MANAGEMENT Recommended minimum setting: 10%. The device, equipped with more than one DALI driver, can be controlled manually with 3F Easy Dim technology or automatically/manually with 3F Smart Dimming technology. DALI Broadcast allows a unique adjustment of the drivers; independent adjustments of DALI driver with addressable DALI systems. In electrical systems without a regulation system (manual or automatic) and DALI bus, a suitable jumper must be made on the DA-DA terminals of the appliance. WARNING Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	46 W	CRI	80
Total flux	5009 lm	LOR	100%
Luminous efficacy	109 lm/W	ULOR	68%
		Total power	46 W

Mounting mode

Pendant

Shape and measurements

Length: 57.80 in  
Width: 2.24 in  
Height: 3.15 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 46 W  
Appliance Class: I

Protection

IP: 40  
IK: 02