

Product data sheet

ARCHITECTURAL LIGHTING
V1-G1-01440-04L22-66020XX FRIEZE 15° X 60° RGBW 20W DMX
VARTON




IP
66

IK
08

Floodlight for architectural illumination. Cast aluminum housing, tempered glass diffuser. Application: architectural light. Installation: surface-mounted. Impact resistance: IK08 Flicker, %: 1 Climatic modification and category of placement: YXJ11 Color rendering index: 80-89 Ingress protection (IP): IP66 Power factor: 0,95 Dimming DMX: Yes <https://www.varton.ru/products/arkhitekturnoe-osveshchenie/frieze/frieze-15-x-60-rgbw/svetodiodnyy-svetilnik-var-ton-arkhitekturnyy-frieze-xs-20-vt-dmx-rgbw-linzovanny-15x60-gradosov-ral/>

Light output 1



1 x LED			
Nominal lamp power	20 W	LOR	100%
Lamp flux	1000 lm	Total flux	1000 lm
Luminous efficacy	50 lm/W	Total power	20 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 5.24 in
Diameter: 6.22 in

Adjustability

Fixed

Electric

System power: 20 W

Protection

IP: 66
IK: 08