Product data sheet


MILO G2 M I GREY 4000K 400MA
7706935
HIDE-A-LITE



IP 65 IK 06

Milo G2 is a dimmable wall-mounted luminaire with a timeless design that provides a smooth and pleasant light distribution on both walls and the ground. Available with both up- and downlight or with downlight only. Equally suitable for entrances, façades, and garages in both residential and public environments. Rated IP65, while the galvanized version is rated IP44. Available in white, grey, black, or galvanized steel, C4. The galvanized version develops a natural patina over time. The backplate is easily mounted to the wall and features dual cable entries (M–XXL) for loop-through wiring. The luminaire can then be conveniently hung in place afterwards. Prepared for surface-mounted cabling (M–XXL). An integrated DIP switch (3000K/4000K) allows adjustment of the colour temperature (M–XXL). Integrated DIP switch for adjustment of luminous flux on sizes M–XXL, excluding S and DALI-2 versions. Replaceable LED module and driver for easy maintenance. Dimmable via phase-cut dimming (S–XXL) or DALI-2 (XXL).

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5.5 W	CRI	90
Total flux	450 lm	LOR	100%
Luminous efficacy	82 lm/W	Total power	5.5 W

Mounting mode

Wall mounted

Shape and measurements

Height: 6.30 in
Diameter: 2.68 in

Adjustability

Fixed

Design

Designer: Elektro Elco AB

Electric

System power: 5.5 W
Appliance Class: I

Protection

IP: 65
IK: 06
Designation labels: CE