
Product data sheet

LD36 19.2W 500MA OB
LD36-C1-500-75-OB-900
LIGHTGRAPHIX



LD36 Surface linear light IP40 / IP54. Constant Current 19.2W 500mA 12° x 36° Oval beam. Offering superb continuous wall washing capabilities from a very compact product, LD36 provides the flexibility to create a range of lit effects in various install applications. From coffer details to seamless shadow free curves, lengths are customisable up to 2100mm and can be specified in wet or dry interior environments, with an optional anti-glare louvre to ensure visual comfort. LD36 features an anodised aluminium body, high-power LED and ultra efficient optics, to deliver excellent beam spread, shape and thermal management.

Light output 1



1 x LED

Nominal lamp power	19.2 W	LOR	100%
Lamp flux	1688 lm	Total flux	1688 lm
Luminous efficacy	88 lm/W	Total power	19.2 W
CCT	3000 K		
CRI	93		

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Length: 35.43 in
Width: 1.18 in
Height: 0.87 in

Adjustability

Fixed

Design

Material impression: Glass, Gloss, Matt, Stainless steel
Color of housing: Black, White, Anthracite / graphite, Silver gray

Electric

System power: 19.2 W
Controller: Dimmable 0..10V, Dimmable 1..10V, DMX, DALI
Appliance Class: III

Protection

IP: 40
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...95°F