

Product data sheet


FIREFLY SURFACE - 4 W - CORRIDOR+ - SMARTSCAN EMERGENCY
WFZ4SCP65
THORLUX LIGHTING



IP
65

Surface mounted emergency luminaires with LiFePO4 battery technology. Surface mounted, IP65 rated emergency luminaires with five optical distribution options for illuminating points of emphasis, escape routes and open areas (anti-panic). Featuring Lithium Iron Phosphate (LiFePO4) battery technology with SmartScan wireless communication versions backed by a 10-year product warranty. Available in 3 W or 4 W power outputs and engineered for easy installation and maintenance. Firefly achieves a 42% reduction in total embodied carbon, reduced energy consumption and a doubled life expectancy compared to the previous model. Applications: industrial and commercial environments, education, healthcare and retail.

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	5.5 W	CRI	80
Total flux	380 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	5.5 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 1.65 in
Diameter: 7.17 in

Adjustability

Fixed

Electric

System power: 5.5 W

Information regarding emergency functions

Emergency lighting only
Emergency sign: N/A

Protection

IP: 65