
Product data sheet


LESS IS MORE 27
312219.002.76
RZB



IP 20

Series: Less is more 27 Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 50 - 60 Hz Housing extruded aluminium profile powder-coated. End caps die-cast aluminium powder-coated. Diffuser aluminium micro-grid in smooth finish (screen-compliant in accordance with EN-12464-1). 2-point steel suspension wires infinitely height-adjustable or required special length on request. External converter with connecting cable. Lamps (LED) included in delivery. Available Colours: white Type of Installation: Pendant Dimensions: L 1512, B 28, H 38 Lamp: LED Life time: 60000 h (L80/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Voltage converter, DALI dim. Safety Marks: F-mark Luminaire flux LED: 2600lm System power: 26W Beam Angle: 65°/45° Number of fittings B10A: 9 Number of fittings B16A: 15 Inrush current: 43A Unified Glare Ratio: 17,5 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	26 W	CRI	80
Total flux	2600 lm	LOR	100%
Luminous efficacy	100 lm/W	Total power	26 W

Mounting mode

Pendant

Shape and measurements

Length: 1.10 in
Width: 59.53 in
Height: 1.50 in

Adjustability

Fixed

Electric

System power: 26 W

Protection

IP: 20