


# Product data sheet

PTECD L20 LE3 & PTECD SSR \*  
 PROTEC LED EMERGENCY  
 DEXTRA




Protec LED - Ø174mm, IP20 Recessed downlighter with ABS housing and bezel, zinc plated spring steel fixing clips, anodised aluminium reflectors. LE3 - Lithium Emergency LS3 - Lithium Selftest LA3 - Lithium Autotest Emergency Lumen Values: No Coloured Ring: Opti-Spec: 367, Opti-Sat: 357 Drop Glass Ring: Opti-Spec: 344, Opti-Sat: 335 IP44 Cover: Opti-Spec: 343, Opti-Sat: 333 Microprism Diffuser: Opti-Spec: 274, Opti-Sat: 263 Opal Diffuser: Opti-Spec: 262, Opti-Sat: 243 S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)\* Replace \* with WH for white ring or GY for Grey

## Light output 1 (integrated, emergency)



Lamp type		CCT	4000 K
Nominal lamp power	4 W	CRI	80
Total flux	388 lm	LOR	100%
Luminous efficacy	97 lm/W	Total power	4 W

## Light output 2 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	16.5 W	CRI	80
Total flux	1859 lm	LOR	100%
Luminous efficacy	113 lm/W	Total power	16.5 W

### Mounting mode

Ceiling recessed

### Shape and measurements

Height: 4.80 in

Diameter: 6.89 in

### Adjustability

Fixed

### Electric

System power: 20.5 W

Ballast: ECG

### Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

## Protection

IP: 20

Designation labels: CE