


# Product data sheet

EMINERE 4 RGBA 15°X90°  
129  
ANOLIS



Eminere was designed by Anolis for a wide range of exterior and interior applications with a variety of lens options that can be used for flood lighting, wall grazing, wall washing and accent lighting. Equipped with Anolis’ unique 18-bit colour mixing resolution ensures extra fine colour tuning as well as smooth dimming at low level of intensity. Designed in our state of the art R&D facility by industry experts with over 10 years experience in their field, Eminere is IP67 rated and can withstand extreme conditions. Eminere is available in 1, 2, 3, and 4 foot sizes (300/600/900/1200 mm) with RGBW, RGBA or PureWhite single chips as standard and is easy to control, 1 pixel per foot. Eminere fixtures can be used for both permanent and temporary installations, including various architectural and architainment applications.

## Light output 1 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	85 W	CRI	84
Total flux	3220 lm	LOR	100%
Luminous efficacy	38 lm/W	Total power	85 W

## Mounting mode

Standing / Bollard, Floor mounted

## Shape and measurements

Length: 48.39 in

Width: 2.99 in

Height: 4.21 in

## Adjustability

Tiltable

## Electric

System power: 85 W

Color adjustable

Appliance Class: I

## Protection

IP: 67

IK: 06