


Product data sheet

VOYAGER C LED AREA MCE E3M WHI
 96548984
 THORN LIGHTING




High performance, surface mounted, 3 hour manual test, emergency lighting luminaire for 1 x 3W LED with open area optic. Housing manufactured from die-cast aluminium, powder coated white. Class I electrical, ingress protection rated IP40. Electrical connection via 2 x 4 x 2.5mm² piano key terminals. Gear and NiMH batteries mounted in body. Two Ø14mm knock-outs on one side to accommodate surface wiring. Suitable for mounting heights up to 7m. Can be operated in either maintained or non-maintained modes. Total power: 5 W Dimensions: 146 x 146 x 37 mm Weight: 0.9 kg

Light output 1 (emergency)



1 x LED			
Nominal lamp power	3 W	LOR	90%
Lamp flux	93 lm	Total flux	84 lm
Luminous efficacy	17 lm/W	Total power	5 W
CCT	3000 K		
CRI	99		

Light output 2



1 x LED			
Nominal lamp power	3 W	LOR	90%
Lamp flux	93 lm	Total flux	84 lm
Luminous efficacy	17 lm/W	Total power	5 W
CCT	3000 K		
CRI	99		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 5.75 in
 Width: 5.75 in
 Height: 1.46 in
 Weight: 0.9 kg

Electric

System power: 10 W
 Voltage: 230-240 V AC
 Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting
 Emergency sign: N/A

Design

Material impression: Aluminum

Color of housing: White

Protection

IP: 40

Designation labels: CE, ENEC