

Product data sheet

VOYAGER C LED AREA MCE E3M WHI


96548984

THORN LIGHTING



High performance, surface mounted, 3 hour manual test, emergency lighting luminaire for 1 x 3W LED with open area optic. Housing manufactured from die-cast aluminium, powder coated white. Class I electrical, ingress protection rated IP40. Electrical connection via 2 x 4 x 2.5mm² piano key terminals. Gear and NiMH batteries mounted in body. Two Ø14mm knock-outs on one side to accommodate surface wiring. Suitable for mounting heights up to 7m. Can be operated in either maintained or non-maintained modes. Total power: 5 W Dimensions: 146 x 146 x 37 mm Weight: 0.9 kg


Light output 1 (emergency)



1 x LED

| | | | |
|--------------------|---------|-------------|-------|
| Nominal lamp power | 3 W | LOR | 90% |
| Lamp flux | 93 lm | Total flux | 84 lm |
| Luminous efficacy | 17 lm/W | Total power | 5 W |
| CCT | 3000 K | | |
| CRI | 99 | | |

Light output 2



1 x LED

| | | | |
|--------------------|---------|-------------|-------|
| Nominal lamp power | 3 W | LOR | 90% |
| Lamp flux | 93 lm | Total flux | 84 lm |
| Luminous efficacy | 17 lm/W | Total power | 5 W |
| CCT | 3000 K | | |
| CRI | 99 | | |

Mounting mode

Ceiling mounted

Shape and measurements

Length: 5.75 in

Width: 5.75 in

Height: 1.46 in

Weight: 0.9 kg

Electric

System power: 10 W

Voltage: 230-240 V AC

Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Design

Material impression: Aluminum

Color of housing: White

Protection

IP: 40

Designation labels: CE, ENEC