Product data sheet

LED SURFACE MOUNTED CEILING SPOT IP65, WHITE, 25W, COLORSWITCH 3000|4000|5000K, DIMMABLE
115594


ISOLED



IP 65

LED surface-mounted ceiling spotlight IP65, white, 25W, ColorSwitch 3000|4000|5000K, dimmable, weatherproof | Dimensioned power: 25 W | Effective power: 24 W | Energy efficiency class: E (EU 2019/2015) | Nominal Voltage: 220 - 240 V AC | Material: aluminum | Surface color: white | Protection class: IP65 | Allowable ambient Temperatures: -20° - 40° C | Diameter: 130 mm | Hole cut-out: 68 mm circle | Beam angle: 70° fixed | Color temperature: 3000K - 5000K | Color rendering index: 80 (Ra 1-8) | Luminous flux: 2300 lm | Phase-on/phase-off dimmable | Suitable for indoor and outdoor use | Useful life: 68000 h (L80|B50) | Guarantee: 3 years | | FABRICATION: ISOLED 115594

Light output 1



1 x LED

Nominal lamp power	24 W	LOR	100%
Lamp flux	2300 lm	ULOR	3%
Luminous efficacy	96 lm/W	Total flux	2300 lm
CCT	3000 K	Total power	24 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.33 in
Diameter: 6.30 in

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 24 W
Ballast: ECG
Integrated Switch: In housing

Protection

IP: 65
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...104°F