

Product data sheet

BRAHE PANEL RE 595X595 2XLINEAR LS 2600 ON/OFF 840 WHITE CWP-2,5M

32208402600

AURA LIGHT




IP
20




Brahe Panel is a LED-panel equipped with two 300x60 mm downlights with the latest LED technology for maximum efficiency and optimal light distribution. Its high-quality lens and reflector technology minimize glare and provide precise and pleasant lighting. INFO to the lighting designer: Please note that the light openings cannot be controlled separately in practice, as both downlights are controlled together by a 1-channel driver. However, it is possible to order a version with separate control upon request.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	9 W	CRI	80
Total flux	1355 lm	LOR	100%
Luminous efficacy	151 lm/W	Total power	9 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	9 W	CRI	80
Total flux	1355 lm	LOR	100%
Luminous efficacy	151 lm/W	Total power	9 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.43 in

Width: 23.43 in

Height: 1.69 in

Adjustability

Fixed

Electric

System power: 18 W

Appliance Class: II

Protection

IP: 20