Product data sheet


FIL45 SUR 1120 4000 9NW D/I OP COMF WH.
F41SF112MOIP940NW
LAMP



IP 20 IK 07

Suspended structure model FIL45 SUR 1120 D/I LAMP brand. Made in extruded recycled aluminum with a rate of 80%, with direct-indirect distribution, with an opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<16 and indirect opal polycarbonate diffuser. Model for LED MID-POWER, colour temperature 4000K with CRI90 and with electronic wiring included. With IP20, IK07 protection rating. Insulation Class I. Photobiological safety group 0. LED life time: 70.000 L80 B10. Available finishes: White, black and grey. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Light output 1



1 x LED

Nominal lamp power	31.7 W	LOR	100%
Lamp flux	2770 lm	Total flux	2766 lm
Luminous efficacy	87 lm/W	Total power	31.7 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 44.09 in
Width: 1.77 in
Height: 3.15 in

Adjustability

Fixed

Electric

System power: 31.7 W
Appliance Class: I

Protection

IP: 20
IK: 07