



Product data sheet

833 CRETA - UGR<LT/>17 4000K CRI 80 30W CLD-D-D WHITE
150240-0041
DISANO



Housing: body in steel sheet and frame in aluminium. Optics: secondary lenses in high-performance and anti-yellowing PMMA. : UGR<lt/>17, according to standard EN 12464. Wiring: quick, no need to open the fixture. LED: 80%: 50000h (L80B20) Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: Ceiling lighting fixture with external driver; it can be easily housed in false ceilings. Mounting: surface mounting on T-beams. Easy installation: quick connection without the need to open the luminaire, can be easily inserted into the ceiling.

Light output 1



1 x LED			
Nominal lamp power	30 W	LOR	100%
Lamp flux	3724 lm	Total flux	3724 lm
Luminous efficacy	124 lm/W	Total power	30 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.43 in
Width: 23.43 in
Height: 1.54 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 30 W
Appliance Class: II

Protection

IP: 40
IK: 06
Designation labels: CE