Product data sheet


RUBIN CLEAN NO FRAME LED 5200 SHM E IP65 34 840 / 1174X274MM
19.4070.2121.34
LUXIONA



IP 65 IK 08

Indoor luminaire. Assembly: surface mounted on ceiling. The body material is steel sheet. Colour - RAL 9016 (white). Dimensions: 1174 x 274 x 69 mm. Weight 7,2 kg. Diffuser: SHM (hardened mat glass). The efficiency of the optical system is 79,10%. Beam angle: (C0-C180) / (C90-C270) - 109,6° / 109,6°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 h L80/B10. Luminaire luminous flux: 4226 lm. Power of luminaire: 27,8 W. Luminaire's light efficiency: 152 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 25 (B10), 40 (B16), 39 (C10), 62 (C16). Operating temperature range: 5 ÷ 30° C. Protection degree: IP65. Impact resistant: IK08. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



4 x LED

Nominal lamp power	6.95 W	LOR	52%
Lamp flux	1336 lm	ULOR	26%
Luminous efficacy	192 lm/W	Total flux	2802 lm
CCT	4000 K	Total power	27.8 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 46.22 in
Width: 10.79 in
Height: 2.72 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 27.8 W
Appliance Class: I

Protection

IP: 65
IK: 08

Other operating numbers

Ambient temperature range: 41...86°F