


Product data sheet

161PX PROXIMA LED DAMP-PROOF LIGHT FITTING VARIO
161PX 06L VARIO ER DV P5X2,5 (16133 1001)
SCHUCH



LED damp-proof light fitting, PROXIMA, 8 W, 21 W, 770 lm, 2860 lm, 96 lm/W, 136 lm/W, Class I, IP65, symmetrical wide beam, 4000 K, CRI≥ 80, Ta -20 °C/+40 °C, L70>100000 h (@ Ta max), L80>70000 h (@ Ta max), L90>50000 h (@ Ta 25°C), Diffuser PMMA satined, Closure Plastic, Housing Glass fibre reinforced polyester, Colour grey, Through wiring (DV) 5x2.5 mm² PVC, enhanced resistance (ER), variable and almost stepless adjustable luminous flux (Attention: only min, max values listed above). Sturdy LED damp-proof light fitting with enhanced protection against corrosive atmospheres and harmful gases and variably adjustable luminous flux. Highly impact-resistant glass fibre reinforced polyester housing and frosted diffuser with high mechanical resistance. Captive safety clips, multi-part, silicone gasket. Powder-coated aluminium reflector with highly efficient Zhaga LED modules and ECG with overload and short circuit protection and switch for toolless setting of the luminous flux. FastFix mounting system with sliding stainless steel mounting clips and brackets for chain suspension. Length 668,00 mm, Width/Diameter 137,00 mm, Height 115,00 mm, Net weight 1,70 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	21 W	CRI	80
Total flux	2860 lm	LOR	100%
Luminous efficacy	136 lm/W	ULOR	7%
		Total power	21 W

Mounting mode

Ceiling mounted, Pendant, Contact rail, Wall mounted

Shape and measurements

Length: 26.30 in

Width: 5.39 in

Height: 4.53 in

Adjustability

Fixed

Electric

System power: 21 W

Appliance Class: I

Protection

IP: 65

IK: 06

Designation labels: CE