


Product data sheet

SMART CAKE 82 LED GE 3000K FLOOD WHITE STRUC
12411509
MODULAR




Smart lighting family Smart Cake, Smart Lotis and Smart Kup form a new generation of spotlights which combine technical ingenuity with timeless design. This family's styling is based on our most popular designs. In concrete terms, the fittings consist of a module which can be combined with one of three trims to suit your requirements. The new spotlights can be combined with Smart Mask or Smart surface box to form the perfect solution for any interior. What you get is a LED module with a different finish. The light flows over the edges of the Smart Cake like its bigger sister.


Light output 1



| | | | |
|--------------------|---------|-------------|--------|
| 1 x LED | | | |
| Nominal lamp power | 13.4 W | LOR | 88% |
| Lamp flux | 994 lm | Total flux | 877 lm |
| Luminous efficacy | 65 lm/W | Total power | 13.4 W |
| CCT | 3000 K | | |
| CRI | 90 | | |



| | | | |
|--------------------|---------|-------------|--------|
| 1 x LED | | | |
| Nominal lamp power | 6.2 W | LOR | 88% |
| Lamp flux | 576 lm | Total flux | 508 lm |
| Luminous efficacy | 82 lm/W | Total power | 6.2 W |
| CCT | 3000 K | | |
| CRI | 90 | | |



| | | | |
|--------------------|---------|-------------|--------|
| 1 x LED | | | |
| Nominal lamp power | 9.2 W | LOR | 88% |
| Lamp flux | 773 lm | Total flux | 682 lm |
| Luminous efficacy | 74 lm/W | Total power | 9.2 W |
| CCT | 3000 K | | |
| CRI | 90 | | |

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.39 in

Diameter: 3.23 in

Adjustability

Fixed

Electric

System power: 6.2-13.4 W

Appliance Class: II

Protection

IP: 20