



Product data sheet

3380 SUSA ME - STREET 3000K CRI 70 54W CLD GREY
340502-39
DISANO



Housing: in die-cast aluminium and designed with a very small surface exposed to wind. Cooling fins integrated in the cover. Attachment: die-cast aluminium with screws for locking the fixture. Suitable for poles with a diameter of 45-60 mm. Optics: in high-performance PMMA resistant to high temperatures and UV rays. Coating: pre-treatment of metal surface, polyester powder coating to ensure resistance to corrosion and salt spray fogs, UV stabilised. Special coating: upon request: available with coating tested to withstand corrosion tests in aggressive artificial atmospheres (UNI EN ISO 9227) or marine environments (sea front). Heat Sink: the heat sink is designed and made to allow the LEDs to operate at temperatures capable of ensuring excellent performance/output and long service life. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. With degree of protection according to EN60529. Equipment: - IP67 quick connector. - anti-condensation valve. - temperature controller with auto-reset. - EN 61547 compliant surge protection. - BASIC PROG built-in functions. On request: - 1-10V dimmable power supply, subcode 12 - virtual midnight device, subcode 30 - power line carrier, subcode 0078 - Nema Socket, subcode 40 - Zhaga Socket, subcode 0054

Light output 1



1 x LED			
Nominal lamp power	54 W	LOR	100%
Lamp flux	7421 lm	Total flux	7421 lm
Luminous efficacy	137 lm/W	Total power	54 W
CCT	3000 K		
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Length: 21.61 in

Width: 6.30 in

Height: 3.19 in

Adjustability

Fixed

Design

Material impression: Aluminum

Electric

System power: 54 W

Appliance Class: II

Protection

IP: 66

IK: 07

Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -22...104°F