Product data sheet


PURE3 SQUARE SUSP. SILVER DI/ID SAT.
P33H14Q-9006C2840L3S
PLANLICHT



IP 20


LED LO 4000K 127,8W 18286lm DALI CRI90 https://katalog.planlicht.com/en-gb/search?q=pure%203

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	31.95 W	CRI	90
Total flux	4572 lm	LOR	100%
Luminous efficacy	143 lm/W	ULOR	34%
		Total power	31.95 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	31.95 W	CRI	90
Total flux	4572 lm	LOR	100%
Luminous efficacy	143 lm/W	ULOR	34%
		Total power	31.95 W

Light output 3 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	31.95 W	CRI	90
Total flux	4572 lm	LOR	100%
Luminous efficacy	143 lm/W	ULOR	34%
		Total power	31.95 W

Light output 4 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	31.95 W	CRI	90
Total flux	4572 lm	LOR	100%
Luminous efficacy	143 lm/W	ULOR	34%
		Total power	31.95 W

Mounting mode

Pendant

Shape and measurements

Length: 58.19 in
Width: 58.19 in
Height: 3.23 in

Adjustability

Fixed

Electric

System power: 127.8 W

Protection

IP: 20