


Product data sheet

FLAT POLYMERO KREIS SLIM
312087.002.1
RZB




IP
40

IK
03

Series: Flat Polymero Kreis Slim Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: push lock. Diffuser: plastic (PMMA), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 515, H 70 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 3100lm System power: 33W Beam Angle: 123° Number of fittings B10A: 53 Number of fittings B16A: 85 Number of fittings C10A: 53 Number of fittings C16A: 85 Inrush current: 0,2A Unified Glare Ratio: 19,9 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	33 W	CRI	80
Total flux	3100 lm	LOR	100%
Luminous efficacy	94 lm/W	ULOR	17%
		Total power	33 W

Mounting mode

Wall mounted

Electric

System power: 33 W

Shape and measurements

Height: 2.76 in
Diameter: 20.28 in

Protection

IP: 40
IK: 03

Adjustability

Fixed