Product data sheet


TUSET L-DOWN LED 5000 LOUVER COPPER / SOUND ABSORBENT RED E 24 840 / S-1,5M
19.4312.3121.24
LUXIONA



IP 40 IK 04

Indoor luminaire. Assembly: surface mounted on slings. The body material is aluminum. Colour - anodised aluminum. Dimensions: 1198 x 168 x 42 mm. Diffuser: LOUVER COPPER (louver in copper). The efficiency of the optical system is 78,66%. Beam angle: (C0-C180) / (C90-C270) - 64,2° / 64,6°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 102000 h L80/B10. Luminaire luminous flux: 4336,1 lm. Power of luminaire: 29,6 W. Luminaire's light efficiency: 146,5 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 15 (B10), 25 (B16), 24 (C10), 38 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0. Luminaire fitted with a PET acoustic panel mounted in the centre of the luminaire, between the louvres.

Light output 1



4 x LED

Nominal lamp power	7.4 W	LOR	52%
Lamp flux	1378 lm	Total flux	2890 lm
Luminous efficacy	186 lm/W	Total power	29.6 W
CCT	4000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 47.17 in
Width: 6.61 in
Height: 1.65 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 29.6 W
Appliance Class: I

Protection

IP: 40
IK: 04

Other operating numbers

Ambient temperature range: 41...95°F