Product data sheet


LIGHTING FOR PRESCHOOL EDUCATIONAL FACILITIES
V1-E0-00300-01OPD-4007030 E300 2.0 IP40 PRE-SCHOOL (1195X595 MM) 70W OPAL DALI
VARTON



IP 40 IK 02

Luminaire for lighting pre-school Educational facilities. Meets all educational lighting requirements and standards. Stainless steel housing with white powder coating. Recessed and surface-mounted. Compatible with the Armstrong Prelude 24 suspended ceiling systems. Input voltage (AC, 50Hz): 176...264 AC frequency: 50 Flicker: 1 Climatic modification and category of placement: УХЛ4 Color rendering index: 90-100 Protection class: I Mounting method: Surface mounting/recessed mounting Ingress protection (IP): IP40 Radiation angle: 120 Impact resistance: IK02 Power factor: 0,95 https://www.varton.ru/products/svetilniki-dlya-doshkolnykh-obrazovatelnykh-uchrezhdeniy/e-seriya-2-0-dlya-doshkolnykh-obrazovatelnykh-uchrezhdeniy/e300-2-0-ip40-doshkolnyy-1195kh595-mm/svetodiodnyy-svetilnik-varton-e300-2-0-dlya-obrazovatelnykh-uchrezhdeniy-70-vt-cri90-3000-k-vstraiva_2/

Light output 1



1 x LED

Nominal lamp power	70 W	LOR	100%
Lamp flux	6650 lm	Total flux	6650 lm
Luminous efficacy	95 lm/W	Total power	70 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 47.05 in
Width: 23.43 in
Height: 1.97 in

Adjustability

Fixed

Electric

System power: 70 W

Protection

IP: 40
IK: 02