


Product data sheet

PURE 1 SPOT CEILING
09.1100/QR-CBC/50W/10°24°38°60°
FLOS




Luminaire for ceiling or three-phase electric track installation. For very low voltage halogen lamps or standar and discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double teflon insulation.

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gx5.3
Lamp flux	1182 lm	LOR	100%
Luminous efficacy	24 lm/W	Total flux	1182 lm
CCT	3000 K	Total power	50 W
CRI	99		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gx5.3
Lamp flux	1054 lm	LOR	100%
Luminous efficacy	21 lm/W	Total flux	1055 lm
CCT	3000 K	Total power	50 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gx5.3
Lamp flux	857 lm	LOR	100%
Luminous efficacy	17 lm/W	Total flux	857 lm
CCT	3000 K	Total power	50 W
CRI	99		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	Gx5.3
Lamp flux	856 lm	LOR	100%
Luminous efficacy	17 lm/W	Total flux	856 lm
CCT	3000 K	Total power	50 W
CRI	99		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 1.69 in

Width: 4.34 in

Height: 5.31 in

Adjustability

Free

Electric

System power: 50 W

Appliance Class: I

Protection

IP: 20