



Product data sheet

STICK LOUVER-LIGHT COLUMN
7290-0-3-436-XX
UNILAMP




STICK is a family of cylindrical-shaped light column and wall luminaire giving symmetrical light distribution on illuminated surfaces. The recommended mounting height is between 3 – 4 meters above ground. It is operated with high power LED. STICK is assembled with anti-glare suppression louvers that direct the light downward onto the illuminated surface. Clear PMMA cover protects the lamp compartment from the ingress of dust and water. It is generally installed in walkways, gardens, parks, commercial areas and open spaces to provide the general lighting from mid-high level. Anchor unit for concrete foundation are is available. spec • Designed, Manufactured and tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium and Extruded Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • PMMA protective cover. • Post-cured silicone gasket. • High quality LED module and driver. • Anodized aluminium louvers. • GFR PA6.6 Terminal block. • Weather proof grommet. • Pole light pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x Compact fluorescent lamp			
Nominal lamp power	42 W	Socket	Gx24Q-4
Lamp flux	3200 lm	LOR	38%
Luminous efficacy	76 lm/W	ULOR	16%
CCT	4000 K	Total flux	1222 lm
CRI	85	Total power	42 W



1 x Compact fluorescent lamp			
Nominal lamp power	42 W	Socket	Gx24Q-4
Lamp flux	3200 lm	LOR	38%
Luminous efficacy	76 lm/W	ULOR	16%
CCT	3000 K	Total flux	1222 lm
CRI	85	Total power	42 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 7.40 in
Width: 7.40 in
Height: 138.98 in

Electric

System power: 42 W
Appliance Class: I

Protection

IP: 65
IK: 10
Designation labels: CE, ENEC

Adjustability

Fixed

Design

Color of housing: White