



Product data sheet

GINO 1 WALL LUMINAIRES
GI-31584-W40
LIGMAN




- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25° C 135,000, 200,000 - Life time L80B10 Ta 50° C 310,000, 490,000 - Die-cast aluminium housing and frame pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear, impact-resistant, toughened glass diffuser - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	2.3 W	CRI	80
Total flux	4 lm	LOR	100%
Luminous efficacy	2 lm/W	Total power	2.3 W

Light output 2 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	2.3 W	CRI	80
Total flux	4 lm	LOR	100%
Luminous efficacy	2 lm/W	Total power	2.3 W

Mounting mode

Wall mounted

Shape and measurements

Length: 3.58 in
Width: 3.94 in
Height: 3.19 in
Weight: 1 kg

Adjustability

Fixed

Glare protection

Glare protection: UGR < 19

Electric

System power: 4.6 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Design

Color of housing: Black, White, Silver gray

Protection

IP: 65

IK: 07

Surface temperature: 40°C