


Product data sheet

LIGHTING FOR ADMINISTRATIVE AND OFFICE BUILDINGS
V1-A0-00420-01OP0-4006040 A420 2.0 IP40 (1495*100 MM) 60W 4000K OPAL
VARTON



Input voltage (AC, 50Hz), V: 176...264 AC frequency, Hz: 50 Flicker, %: 2 Climatic modification and category of placement: УХЛ4 Height/depth, mm: 50 Length, mm: 1 495 Protection class: I Ingress protection (IP): IP40 Impact resistance: IK03 Width, mm: 100 Power factor: 0,95
<https://www.varton.ru/products/ofisnoe-osveshchenie/a-seriya-2-0/a420-2-0-ip40-ofis-1495-100/svetodiodnyy-svetilnik-var-ton-a420-2-0-ofisnyy-60-vt-vstraivaemyy-nakladnoy-4000-k-1495kh100kh50-mm-/>

Light output 1



1 x LED			
Nominal lamp power	60 W	LOR	100%
Lamp flux	6300 lm	Total flux	6300 lm
Luminous efficacy	105 lm/W	Total power	60 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 58.86 in
Width: 3.94 in
Height: 1.97 in

Adjustability

Fixed

Electric

System power: 60 W

Protection

IP: 40
IK: 03