



Product data sheet

SRT-SYSTEM IP20-SRGVCG EP/1500 LED - GERÄTETRÄGER VARIABEL CENTRAL.LINE.OPTIC GEEIST | DEVICE MOUNT VA.
13000-8000 830 10486LM ETM SG RAL 9006 (SRT+19575004895)
REGIOLUX



SRT-Quick-fit mounting system, Variable device mount, Modullänge/1500. Device mount made of a galvanised, profiled steel sheet; surface coated with polyester resin. Tool-free attachment with design-integrated pressure caps guarantee protection against theft and dismantling. Variable position on the mounting rail. Housing colour silver grey/white aluminium RAL 9006. Performance level: Economy Performance (EP) - For cost-sensitive projects, high efficiency and a long service life, Light distribution direct/indirect diffuse distribution by means of Central.Line.Optic frosted of PMMA plastic, the lens optics ensure absolute ease of assembly and are simple to maintain thanks to the easily cleaned surface. The compact 1-row arrangement of the lenses ensures that the dots merge into a line with a homogeneous appearance in the object. The light source and driver are removable in accordance with the EU 2019/2020 ecodesign requirements and can be replaced in the factory. Electrical connection by means of a 1m connection cable for variable device mount positioning with a 3-pin, quick-fit plug connector in the light run with free phase pre-selection. The device mount can be adjusted variably in steps with a multi-lumen driver. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system. Additional information on the driver switching stages is available on the Internet on the product details page or in the product data sheet under the heading Operating Data. Dimensions (LxWxH): 1531mm x 55mm x 37mm Beam angle: 105°(C0)/110° (C90) Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 3000K Colour tolerance: 3SDCM Photobiological safety (Luminaire): RG1 LED service life: 50000h L80/B10 (Tq 25°C), 50000h L90/B50 (Tq 25°C) Nominal luminous flux/switching steps (rounded): 11700lm/89W, 10500lm/77W, 9200lm/66W, 7300lm/50W (Standard setting 11737lm) Luminaire luminous efficiency: 146lm/W-132lm/W Control gear: Electronic multi-lumen driver, 4-steps (1 pcs.) System output: 89W-50W Energy efficiency class/light source: C Mains voltage: 230V Mains frequency: 50Hz Impact resistance (IK rating): IK03 (-20°C bis 25°C) Ambient temperatur: ta - 20°C to 25°C UGR lat./long.: 27.7 / 28.3 (89W) Certification mark: IP20, Protection class I, ENEC10 VDE, F, HACCP DIN10500/Food/IFS-application-related suitability (see certificate)/BRC, Indoor, CE Warranty period: 5 years Regiolux GmbH Type: SRGVCG EP /1500 LED 13000-8000 830 ETM sg RAL 9006 Article number: 19575004895 Product deep link: <https://www.regiolux.de/en/article/19575004895> General warranty conditions: www.regiolux.de/en/Service/Warranty

Light output 1 (integrated)



Lamp type		CCT	3000 K
Nominal lamp power	77.3 W	CRI	80
Total flux	10486 lm	LOR	100%
Luminous efficacy	136 lm/W	Total power	77.3 W

Mounting mode

Ceiling mounted, Contact rail

Electric

System power: 77.3 W
Appliance Class: 0

Shape and measurements

Length: 60.43 in

Width: 2.48 in

Height: 2.64 in

Design

Color of housing: Silver gray

Protection

IP: 20

IK: 03

Designation labels: CE, ENEC