


Product data sheet

MERCMASTER LED LT 5500 LUMEN NEMA TYPE I 4000 K CCT DIFFUSED PC GLOBE
 I/MLTAL52ND1
 APPLETON (EMERSON EGS)



Mercmaster LED LT Series Pendant/ Ceiling Mount 3/4" NPT Hub Diffused Polycarbonate Globe NEMA Type I 4000 K CCT/ 80 CRI Voltage- BU-120-277V, 50/60Hz, 125-300 Vdc BH-347-480 Vac, 50/60Hz Class I, Division 2, Groups A, B, C, D Class I, Zone 2, AEx ec IIC Zone 21, AEx tb IIIC Class I, Zone 2, Ex ec IIC Class II, Division 1, Group E, F, G Zone 20, Group IIIC Class II, Division 2, Group F, G Class III Simultaneous Exposure Type 3R, 4X IP66 Suitable for Use in Wet Locations Marine Outside Type (Salt Water) DLC Qualified Product listed Refer to catalog for additional options

Light output 1 (integrated)



Lamp type	LED	CCT	3783 K
Nominal lamp power	46.1 W	CRI	84
Total flux	4527 lm	LOR	100%
Luminous efficacy	98 lm/W	ULOR	3%
		Total power	46.1 W

Mounting mode

Pendant

Shape and measurements

Height: 1.00 in

Diameter: 7.50 in

Adjustability

Fixed

Electric

System power: 46.1 W

Appliance Class: II

Protection

IP: 67

Explosion zone suitability: 2, 20, 21