

Product data sheet


TUBILUX XT 4500-840 PM L1285 EVG TW
42186408
ZUMTOBEL



IK
07

Tube luminaire with through-wiring with \varnothing 90 mm, Luminaire luminous flux: 4519 lm, Luminaire efficacy: 141 lm/W. Colour rendering Ra > 80, colour temperature 4000 K. Total power: 32 W, with LED converter; LED service life lasts 73000 h before luminous flux is reduced to 80% of the initial value. Chromaticity tolerance (initial MacAdam): 3. suitable for ceiling mounting and horizontal or vertical wall mounting. Approved for indoor use and in unprotected outdoor areas. ambient temperature: -30°C to +50°C. Housing of impact-resistant (IK07) polymethylmethacrylate, satin, and end caps of polyamide (PA). Age-resistant silicon seal (SI). Gear tray of double coated sheet steel, white. Flexible mounting with stainless steel fixing clips. Electrical connection via cable gland with integrated pressure equalisation element and plug connection terminal. IFS/BRC-compliant. Luminaire wired with halogen-free leads. IPX9K... Dimensions: 1285 x 90 x 105 mm weight: 3.6 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	32 W	CRI	80
Total flux	4519 lm	LOR	100%
Luminous efficacy	141 lm/W	ULOR	6%
		Total power	32 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 50.59 in
Width: 3.54 in
Height: 4.13 in
Weight: 3.6 kg

Design

Material impression: Plastic

Electric

System power: 32 W
Voltage: 220-240 V AC

Protection

IK: 07