


Product data sheet

LED RECESSED PANEL AREO VARIFIT IP44 3-STEP DIMMING SQUARE MM WHITE 4,000K
93060
PAULMANN




The rectangular Areo recessed panel with a size of 230x230mm and an output of 16 watts in White provides extensive warm white light. Thanks to flexible VariFit technology, the clamping springs can be freely adjusted between 50 and 195 mm for installation. The panel can therefore be installed both in existing boreholes and new ones created with standard drill bits. The integrated 3-step dimming function offers three dimming levels in combination with a regular commercial light switch. The memory function stores the most recently used level until next activation. For hole diameters larger than 85 mm, a cavity depth of at least 30 mm is needed. For hole diameters larger than 68 mm, a depth of at least 55 mm is needed.

Light output 1



1 x LED			
Nominal lamp power	20 W	LOR	100%
Lamp flux	1698 lm	Total flux	1697 lm
Luminous efficacy	85 lm/W	Total power	20 W
CCT	4000 K		
CRI	84		



1 x LED			
Nominal lamp power	16 W	LOR	100%
Lamp flux	1 lm	Total flux	1 lm
Luminous efficacy	0 lm/W	Total power	18 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 9.06 in

Width: 9.06 in

Height: 1.02 in

Weight: 0.57 kg

Adjustability

Fixed

Electric

System power: 18-20 W

Appliance Class: II

Protection

IP: 44

Designation labels: CE

Other operating numbers

Ambient temperature range: 39...39°F

Design

Material impression: Aluminum, Glass, Plastic, Stone

Color of housing: Silver gray, White, Black, Gold, Anthracite / graphite