


# Product data sheet

PRO-LINE RETROFIT II 90°  
40640402  
PROLUMIA




Light source: SMD 2835 LED Illumination angle: 90° Color temperature: 4000K Color rendering index: Ra > 80 Operating temperature: -25°C – +45°C Number of burning hours: L80B50 > 100,000 / L90B50 > 50,000 LED power supply (included): CE Supply voltage: 220-240V AC 50/60Hz Electrical safety class: Class I Supply voltage: 220 - 240V AC 50-60Hz Safety class: Class I

## Light output 1




### 1 x LED

Nominal lamp power	23 W	LOR	100%
Lamp flux	3840 lm	Total flux	3840 lm
Luminous efficacy	167 lm/W	Total power	23 W
CCT	4000 K		
CRI	80		




### 1 x LED

Nominal lamp power	73 W	LOR	100%
Lamp flux	11500 lm	Total flux	11500 lm
Luminous efficacy	158 lm/W	Total power	73 W
CCT	4000 K		
CRI	80		




### 1 x LED


Nominal lamp power	63 W	LOR	100%
Lamp flux	10050 lm	Total flux	10050 lm
Luminous efficacy	160 lm/W	Total power	63 W
CCT	4000 K		
CRI	80		




<b>1 x LED</b>			
Nominal lamp power	53 W	LOR	100%
Lamp flux	8625 lm	Total flux	8625 lm
Luminous efficacy	163 lm/W	Total power	53 W
CCT	4000 K		
CRI	80		




<b>1 x LED</b>			
Nominal lamp power	43 W	LOR	100%
Lamp flux	7150 lm	Total flux	7150 lm
Luminous efficacy	166 lm/W	Total power	43 W
CCT	4000 K		
CRI	80		



<b>1 x LED</b>			
Nominal lamp power	39 W	LOR	100%
Lamp flux	6625 lm	Total flux	6625 lm
Luminous efficacy	170 lm/W	Total power	39 W
CCT	4000 K		
CRI	80		



<b>1 x LED</b>			
Nominal lamp power	35 W	LOR	100%
Lamp flux	5750 lm	Total flux	5750 lm
Luminous efficacy	164 lm/W	Total power	35 W
CCT	4000 K		
CRI	80		



<b>1 x LED</b>			
Nominal lamp power	28 W	LOR	100%
Lamp flux	4670 lm	Total flux	4670 lm
Luminous efficacy	167 lm/W	Total power	28 W
CCT	4000 K		
CRI	80		

**Mounting mode**

Ceiling recessed, Pendant, Contact rail

**Shape and measurements**

Length: 60.12 in

Width: 2.52 in

Height: 1.93 in

**Electric**

System power: 23-73 W

Appliance Class: 0

## Protection

IP: 40

IK: 06

Designation labels: CE