Product data sheet


MODSEC L68 E3
MOD SECURE EMERGENCY
DEXTRA



IP 40 IK 10


MOD Secure - 600x600, IP40, IK10 Recessed pull-up luminaire, white powder coated steel body, designed to be compliant with the requirements of the Department of Health Environmental Guide, Adult Medium Secure Services when installed with anti-pick mastic. Options: E3 - Emergency control gear (511 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* H - High Frequency Dimming (Analogue 1-10v)

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	4.5 W	CRI	80
Total flux	511 lm	LOR	100%
Luminous efficacy	114 lm/W	Total power	4.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	38 W	CRI	80
Total flux	4760 lm	LOR	100%
Luminous efficacy	125 lm/W	Total power	38 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.62 in
Width: 23.62 in
Height: 4.41 in

Adjustability

Fixed

Electric

System power: 42.5 W
Ballast: ECG
Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 40

IK: 10

Designation labels: CE