

Product data sheet

NORA I (WALL FITTING)
9.741.2152.05
LEIPZIGER LEUCHTEN



IP
55

For medium light requirements, mounting height 3.50 - 4.00 m. - Impact-resistant clear or beaded polycarbonate attachment, UV-stabilized - Special reflector of premium highest-grade aluminium, burnished and anodized, for excellent illumination and glare protection -Aluminium luminaire body, inside finished in white paint, outside painted in colour - Aluminium unit carrier, painted white - Adapter jack connection - Available in any RAL or DB colour without surcharge - Scope of delivery includes special steel post/wall-mounted bracket, painted Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lamp

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 50 W | LOR | 76% |
| Lamp flux | 3500 lm | ULOR | 2% |
| Luminous efficacy | 43 lm/W | Total flux | 2667 lm |
| CCT | 2000 K | Total power | 62 W |
| CRI | 25 | | |



1 x High pressure sodium vapour lamp

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 70 W | LOR | 76% |
| Lamp flux | 5600 lm | ULOR | 2% |
| Luminous efficacy | 51 lm/W | Total flux | 4268 lm |
| CCT | 2000 K | Total power | 83 W |
| CRI | 25 | | |

Mounting mode

Wall mounted

Shape and measurements

Height: 21.26 in
Diameter: 21.26 in

Electric

System power: 62-83 W

Protection

IP: 55