


Product data sheet

KRONOS - SURFACE WASHER / BI-SYMMETRIC
2371-G-3-669-XX
UNILAMP



A new family of Area Light, Surface Washer and Flood Light in various mounting application KRONOS utilizes the latest LED technology from renowned manufacturers with high CRI in both 3000K and 4000K with the power classes from 87W to 170W. The high level of die-cast aluminium housing is filmed with Nano Ceramic and coated with super durable double layer coating. The heat management has been delicately designed and tested under ambient thermal condition Ta 40°C - 50°C. A calibrated aiming unit provides accuracy of the light distribution on any surface or structure. KRONOS offers various light distribution patterns e.g. Asymmetric Flat Beam (Road Optic) for European, USA and Asian streets regulations, Asymmetric Forward Throw for squares and open spaces, as well as Narrow, Medium, Wide and Elliptical beams for Flood Lighting application.

Light output 1



1 x LED			
Nominal lamp power	127 W	LOR	100%
Lamp flux	24320 lm	ULOR	7%
Luminous efficacy	192 lm/W	Total flux	24320 lm
CCT	4000 K	Total power	136 W
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 7.95 in
Width: 7.95 in
Height: 7.72 in

Adjustability

Free

Electric

System power: 136 W
Appliance Class: I

Protection

IP: 65
IK: 07