# Product data sheet


BURAN-L2WG6-LC-W1-32LED-3000K-4860LM-32.1W
LIGHTRONICS



IK 10

BURAN EXL GUIDANCE LIGHTING EXL stands for external lenses. The lenses of the BURAN EXL are placed on the outside of the luminaire. This design provides efficient lighting where needed, and also acts as guidance lighting. The BURAN EXL features tilt adjustment to shine the light beam exactly where you need it under all circumstances. The BURAN EXL can be supplied with any dimming program you specify. This keeps your energy consumption low. The luminaire is easy to mount, install and maintain.

## Light output 1



### 32 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 1.003 W | LOR | 87% |
| Lamp flux | 152 lm | Total flux | 4219 lm |
| Luminous efficacy | 151 lm/W | Total power | 32.1 W |
| CCT | 3000 K | | |
| CRI | 70 | | |

### Mounting mode

Pole integrated

### Shape and measurements

Length: 23.62 in
Width: 9.45 in
Height: 5.12 in

### Adjustability

Fixed

### Design

Material impression: Aluminum
Color of housing: Black, Anthracite / graphite, Silver gray

### Electric

System power: 32.1 W

### Protection

IK: 10