


Product data sheet


SUPERLINEA SYSTEM 1152 UP LED 9.6W RA98 4000K 230V/50HZ IP40 BATWING - UP 75MA
 723-71-UP-20-84-B
 EXENIA



IP
40


The new polyspherical or linear fly-eye optics have made it possible to conceive innovative lighting units with absolutely unique size/performance ratios. The Superlinea project aims to make system composition easy and intuitive by offering simple pre-assembled modules, with driver on board, to be connected in sequence with quick couplings and very few additional elements. The configurations offered are divided between: linear modular system in ceiling or suspension mode and simplified stand-alone, ceiling or suspension mode. We have prioritised longitudinal and transverse visual comfort in order to achieve consistently low UGR factors and efficiencies in the region of 140 lumens/W, while maintaining the slim, minimalist design typical of the Exenia style. Each suspended unit is available in single-emission and bi-emission modes

Light output 1



1 x LED			
Nominal lamp power	10.8 W	LOR	100%
Lamp flux	1196 lm	ULOR	100%
Luminous efficacy	111 lm/W	Total flux	1196 lm
CCT	4000 K	Total power	10.8 W
CRI	98		

Light output 2



1 x LED			
Nominal lamp power	10.8 W	LOR	100%
Lamp flux	1196 lm	ULOR	100%
Luminous efficacy	111 lm/W	Total flux	1196 lm
CCT	4000 K	Total power	10.8 W
CRI	98		

Mounting mode

Pendant

Shape and measurements

Length: 0.94 in
 Width: 121.10 in
 Height: 22.68 in

Electric

System power: 21.6 W

Protection

IP: 40

Adjustability

Fixed