


Product data sheet

DIGISTREET CATENARY BTP764 T25 1 XLED110-4S/740 DSM1
BCP764
PHILIPS



Get your city ready for the future with DigiStreet Philips DigiStreet Catenary is a new member of the DigiStreet Road & Street family, and it enables you to benefit from the same lighting quality, distinctive design and the advantages of connected lighting systems in applications requiring catenary solutions. Supporting Smart City initiatives, the full DigiStreet range can be equipped with two System Ready (SR) sockets to enable your city to opt in for existing and future controls, sensors and applications such as the Philips CityTouch remote light management system. In addition, each individual luminaire is uniquely identifiable, thanks to the Philips Service tag, which is based on QR coding. With a simple scan of the QR code, which is located on the inside of the mast door, you gain instant access to the luminaire configuration, making maintenance and programming operations faster and easier, throughout the luminaire's entire lifetime.

Light output 1



1 x LED			
Nominal lamp power	67 W	LOR	90%
Lamp flux	11000 lm	Total flux	9873 lm
Luminous efficacy	147 lm/W	Total power	67 W
CCT	4000 K		
CRI	70		

Mounting mode

Pole top mounted

Electric

System power: 67 W

Shape and measurements

Length: 22.83 in

Width: 20.51 in

Height: 10.28 in