Product data sheet


2W 3000K DOUBLE
L08
MP LIGHTING



IP 66

Application Exterior/Interior directional in-grade light for lighting walls, columns, architectural features or landscape features. Applicable for mounting into floors, walls, ceilings or other surfaces where a non-obtrusive luminaire is required. IP Rating 66 Mounting Comes with splice box, aluminum flange and level gauge. Can be buried in earth/gravel or cast into concrete/paving stone with or without mounting base. Can be mounted with MK1 and MK2 (consult with factory). Can be used with Single Gang Box 2 (not included, can be purchased directly from MP Factory) Electrical Powered by remote dimmable/non-dimmable driver(sold separately). *See website for recommended drivers *Remote emergency driver / inverter options available. Consult factory Power Consumption 1.5 Watt (at 350 mA, 1.0 Watt) 3.0 Watt (at 700 mA, 2.5 Watt) Light Output 1.0 Watt, 0.5~1lm 2.5 Watt, 0.8~1.6lm Warranty 5 years limited warranty Estimated useful life of LED is 50,000 hours. Material Solid anodized aluminum or stainless steel (316), suitable for walk-over and drive-over applications. RoHS compliant. Weight 1.8lbs (0.816kg), base extra.

Light output 1



1 x LED

Nominal lamp power	2 W	LOR	1%
Lamp flux	2 lm	Total flux	0 lm
Luminous efficacy	0 lm/W	Total power	2.5 W
CCT	3000 K		
CRI	80		

Mounting mode

Floor recessed

Shape and measurements

Length: 2.44 in
Width: 2.44 in
Height: 0.20 in

Adjustability

Fixed

Electric

System power: 2.5 W

Protection

IP: 66