
Product data sheet

1795 FARO 5 AS - TALL ASYMMETRIC 4000K CRI 80 4W CLD GRAPHITE
510650-00
DISANO



Housing: in extruded aluminium, with cylindrical cross-section with a diam. of 180 mm. Base: in die-cast aluminium. Diffuser: in polycarbonate, transparent, anti-glare, shatterproof and V2 self-extinguishing, UV stablised. Coating: the fully automated powder-coating cycle involves a polyester-based, salt-spray corrosion-resistant and UV-stabilised paint. Special coating: Upon request: protective coating recommended for marine environments within 5 km (3 miles) of the sea. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. They have a degree of protection according to the EN60529 standard. Equipment: - with air circulation valve. - complete with waterproof connector for line connection.n

Light output 1



1 x LED

Nominal lamp power	4 W	LOR	100%
Lamp flux	250 lm	Total flux	250 lm
Luminous efficacy	62 lm/W	Total power	4 W
CCT	4000 K		
CRI	80		

Mounting mode

Standing / Bollard

Shape and measurements

Height: 34.45 in
Diameter: 7.09 in

Adjustability

Fixed

Design

Color of housing: Anthracite / graphite

Electric

System power: 4 W
Appliance Class: II

Protection

IP: 65
IK: 10
Designation labels: CE