

Product data sheet

FLAT POLYMERO
311518.002.5.76
RZB




IP
40

IK
03

Series: FLAT POLYMERO Decorative round surface-mounted luminaire. Base: metal, powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Diffuser fastening: patented push system. Suitable for ceiling mounting, wall (surface). Colour: white Diameter: 460 mm Height: 120 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 19 W Rated luminous flux: 2100 lm Luminous efficiency: 111 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 40

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 19 W | CRI | 80 |
| Total flux | 2100 lm | LOR | 100% |
| Luminous efficacy | 111 lm/W | ULOR | 10% |
| | | Total power | 19 W |

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.72 in
Diameter: 18.11 in

Adjustability

Fixed

Electric

System power: 19 W

Protection

IP: 40
IK: 03