



Product data sheet

ARUNA SLIM M LED 8000 OPTICS-3L E 34 840 / L-1200
19.3045.0303.34
LUXIONA



Indoor luminaire. Assembly: mounted in module ceilings or using an adaptor frame in plasterboard ceilings. The body material is steel sheet. Colour - RAL 9016 (white). Luminaire dimensions: 1193 x 80 x 43 mm. Weight 2,84 kg. Diffuser: OPTICS (optical system based on lenses). The efficiency of the optical system is 76,43%. Beam angle: asymmetric light distribution - $I_{max}=-18^{\circ}$. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 (1) / 147000 (2) h L80/B10 (1) / L70/B50 (2). Luminaire luminous flux: 6367 lm. Power of luminaire: 57 W. Luminaire's light efficiency: 111,7 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor $\cos\phi$: >0,95. Circuit load capacity: 16 (B10), 26 (B16), 23 (C10), 37 (C16). Operating temperature range: 5 ÷ 30° C. Protection degree: IP20. Impact resistant: IK04. Protection against electric shock: I.

Light output 1



2 x LED			
Nominal lamp power	28.5 W	LOR	83%
Lamp flux	4165 lm	Total flux	6953 lm
Luminous efficacy	146 lm/W	Total power	57 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 46.97 in

Width: 3.15 in

Height: 1.69 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 57 W

Appliance Class: I

Protection

IP: 20

IK: 04

Other operating numbers

Ambient temperature range: 41...86°F