
Product data sheet


X-LINE SLIGHT LOW UGR L-DOWN LED 2400 LOUVER E 34 840 LINE-BM / L-1598MM S-1,5M
19.4420.7521.34
LUXIONA



IP 40 IK 04

Indoor luminaire. Assembly: surface mounted on slings. The body material is aluminum. Colour - RAL 9016 (white). Dimensions: 1598 x 34 x 68 mm. Diffuser: LOUVER (anti-glare louver). The efficiency of the optical system is 71,66%. Beam angle: (C0-C180) / (C90-C270) - 46° / 44,6°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 145000 h L90/B10. Luminaire luminous flux: 1782,5 lm. Power of luminaire: 14,5 W. Luminaire's light efficiency: 122,9 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 25 (B10), 40 (B16), 39 (C10), 62 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



1 x LED

Nominal lamp power	14.5 W	LOR	52%
Lamp flux	2486 lm	Total flux	1304 lm
Luminous efficacy	171 lm/W	Total power	14.5 W
CCT	4000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 62.91 in
Width: 1.34 in
Height: 2.68 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 14.5 W
Appliance Class: I

Protection

IP: 40
IK: 04

Other operating numbers

Ambient temperature range: 41...95°F